

## 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

General Name:	<table border="1"> <thead> <tr> <th colspan="3">HMIS III</th> </tr> </thead> <tbody> <tr> <td colspan="3">AF982 Pressure Sensitive Aluminum Foil Tape</td> </tr> <tr> <td>HEALTH</td> <td>/</td> <td>1</td> </tr> <tr> <td>FLAMMABILITY</td> <td></td> <td>1</td> </tr> <tr> <td>PHYSICAL HAZARD</td> <td></td> <td>0</td> </tr> <tr> <td>PERSONAL PROTECTION</td> <td></td> <td>B</td> </tr> </tbody> </table>		HMIS III			AF982 Pressure Sensitive Aluminum Foil Tape			HEALTH	/	1	FLAMMABILITY		1	PHYSICAL HAZARD		0	PERSONAL PROTECTION		B
HMIS III																				
AF982 Pressure Sensitive Aluminum Foil Tape																				
HEALTH	/	1																		
FLAMMABILITY		1																		
PHYSICAL HAZARD		0																		
PERSONAL PROTECTION		B																		
<b>AF982 Pressure Sensitive Aluminum Foil Tape</b>	Icons: None																			
Shurtape Technologies, LLC																				
PO Box 1530																				
Hickory, NC 28603-1530																				
(828) 322-2700																				
Prepared Date: 19 June, 2008	Prepared By: EHS Group																			
24-Hour Emergency Phone Number																				
CHEMTREC -1-800-424-9300	CHEMTREC Customer Number: 20165																			

## 2. COMPOSITION / INFORMATION ON INGREDIENTS

<u>Ingredient</u>	<u>CAS Number</u>	<u>% Weight</u>
Foil/Scrim/Kraft Backing	Proprietary	40-50 %
Synthetic Rubber Adhesive	Proprietary	50-60 %

## 3. HAZARDS IDENTIFICATION

### Emergency Overview

May cause skin or eye irritation by mechanical abrasion or by sensitivity to polymers.

Note: If this product is subject to combustion it will undergo hazardous decomposition that will yield the formation and release of hazardous substances including but not limited to carbon dioxide, carbon monoxide, polycyclic organic matter, and smoke. Exposure may cause irritation of the eyes, skin, and respiratory tract. Symptoms such as coughing, tearing, and irritation should be regarded as potentially hazardous and measures should be taken to avoid exposure.

## 4. FIRST AID MEASURES

### Eyes

If wearing contact lenses, remove. Hold eyelids apart and immediately flush eyes with plenty of low-pressure water for at least 15 minutes. Get medical attention if irritation persists.

### Skin

Wash with soap and water. Seek medical attention if irritation develops or persists.

### Ingestion:

Do not give anything by mouth to an unconscious person. Seek medical attention.

Shurtape Technologies, LLC PO Box 1530 Hickory, NC 28603-1530 USA Phone 1.888.442.TAPE (8273) Fax 800.335.7651  
www.shurtape.com

ISO 9000 CERTIFIED QUALITY SYSTEM

## Inhalation

Not applicable.

## 5. FIRE FIGHTING MEASURES

Flash Point (°F)	<i>Not Determined</i>
LEL	<i>Not Determined</i>

Auto Ignition Temp (°F)	<i>Not Determined</i>
UEL	<i>Not Determined</i>

### Hazardous Products of Combustion

If this product is subject to combustion it will undergo hazardous decomposition that will yield the formation and release of hazardous substances including but not limited to carbon dioxide, carbon monoxide, polycyclic organic matter, and smoke.

### Fire and Explosion Hazards

Minimal fire hazard as supplied. Polymers in adhesive and polymer backed cloth will support combustion.

### Extinguishing Media

X	Foam	X	Water Spray	X	CO2	X	Dry Chemical
---	------	---	-------------	---	-----	---	--------------

### Fire Fighting Instruction

Wear a self-contained breathing apparatus with a full face piece operated in the positive pressure demand mode with appropriate turn-out gear and chemical resistant personal protective equipment.

## 6. ACCIDENTAL RELEASE MEASURES

Not applicable.

## 7. HANDLING AND STORAGE

### Handling

Material will be tacky/sticky. Recommend the use of light weight cloth or leather gloves for actual handling of material.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### Eye Protection

Safety glasses with side-shields recommended

### Skin Protection

Normal lightweight work clothing will minimize skin contact. Use of lightweight cloth or leather gloves recommended.

### Respiratory Protections

No adverse respiratory exposure anticipated under normal use

## Engineering Controls

No special engineering controls are required

## Exposure Guidelines

Not applicable

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point	N/A	Melting Point	N/A
Specific Vapor Density	N/A	Percent Volatiles	<1%
Specific Gravity	N/A	Evaporation Rate	N/A
Appearance	Silver	State	Solid at Ambient Temperature
Odor	No Strong odor	pH	N/A
Viscosity	N/A	Freezing Point	N/A
Molecular Weight	N/A	Solubility in H <sub>2</sub> O	negligible

## 10. STABILITY AND REACTIVITY

### Hazardous Polymerization

Not anticipated under normal or recommended handling, use, or storage conditions.

### Hazardous Decomposition

None anticipated under normal or recommended handling, storage, and use conditions.

If this product is subject to combustion it will undergo hazardous decomposition that will yield the formation and release of hazardous substances including but not limited to carbon dioxide, carbon monoxide, polycyclic organic matter and particulate matter. This is not the intended use for this product.

### Chemical Stability

Stable

### Incompatibility

Incompatible with: strong acids and oxidizing agents

## 11. TOXICOLOGICAL INFORMATION

Exposure to chemicals and possible effects will not occur with normal use.

## 12. ECOLOGICAL INFORMATION

No Data

## 13. DISPOSAL CONSIDERATION

## Waste Management Information

This material is considered to be non-hazardous under EPA's RCRA regulations. Dispose of per appropriate local regulations. Product is not recyclable.

## 14. DOT Information – 49 CFR 172.101

### DOT description:

Material is not a hazardous material when shipped

### Container / Mode:

Various size packages can be utilized for shipping this material

### NOS Component:

None

### RQ (Reportable Quantity) – 49 CFR 172.101

Product Quantity (lbs) - None

### Other Transportation Information

The DOT Transport Information may vary with the container and mode of shipment

## 15. REGULATORY INFORMATION

### US Federal Regulations

#### TSCA (Toxic Substances Control Act) Status

TSCA (UNITED STATES) The intentional ingredients of the product are listed.

#### DSL (Canada)

The intentional ingredients of this product are listed.

#### CERCLA RQ – 40 CFR 302.4 (a)

None

#### CERCLA RQ – 40 CFR 302.4 (b)

None

#### SARA 302 Components 0 40 CFR 355 Appendix A

None

#### Section 311 / 312 Hazard Class – 40 CFR 370.2

Immediate (X) Delayed ( ) Fire (X) Reactive ( ) Sudden Release of Pressure ( )  
Immediate for the molten liquid state only

## OSHA Process Safety Management 29 CFR 1910

None listed

## EPA Accidental Release Prevention 40 CFR 68

None listed

## State and Local Regulations

### California Proposition 65

The following statement is made in order to comply with the California Safe Drinking Water and Toxic Enforcement Act of 1986<>Use of Shurtape Pressure Sensitive Tape products poses no significant risk as defined by California Proposition 65<>

### EU Directives

94/62/EC – Packaging and Packaging Waste Directive and CONEG Model legislation for the restriction of metals in packaging. Complies with standard of less than 100 PPM total concentration Cd, Cr<sup>+6</sup>, Hg, and Pb.

2002/95/EC – Restriction on the use of certain hazardous substances in electrical and electronic equipment. Complies with this standard with less than 100 PPM total concentration Cd, Cr<sup>+6</sup>, Hg, and Pb. This product does not utilize brominated flame retardants.

## 16. OTHER INFORMATION

### US Green Building Council – LEED®

The following information addresses the allowable credits that may be claimed in accordance with Green Building Rating System for New Construction and Major Renovations, version 2.2

**Indoor Environmental Quality:** EQ Credit 4.1: Low-Emitting Materials (p. 69):

Adhesives & Sealants: Substrate Specific Applications:

Metal to Metal: VOC content < 30 g/l [in accordance with SCAQMD Rule #1168]

Actual VOC content: < 25 g/l [based upon testing conducted in accordance with SCAQMD Rule #1168]

Credit: 1 point

The following information addresses the allowable credits that may be claimed in accordance with LEED® for Homes Rating System

**Materials and Resources:** MR Credit 2.2: Environmentally Preferable Products:

Table 24 – Environmentally Preferable Products : Adhesives and Sealants (see Table 26)

Table 26 – Standards for Low-Emissions Adhesives and Sealants (meet SQAQMD Rule #1168)

Substrate Specific Applications:

Metal to Metal: VOC content < 30 g/l [in accordance with SCAQMD Rule #1168]

Actual VOC content: < 25 g/l [based upon testing conducted in accordance with SCAQMD Rule #1168]

Credit ½ point

As defined by the Code of Federal Regulations 1910. 1200, this product is considered to be an article, defined in the regulation as a “manufactured item other than a fluid or particle: (I) which is formed to a specific shape or design during manufacture; (II) has an end use function(s) dependent in whole or in part upon its shape or design during end use; and (III) which does not

Shurtape Technologies, LLC PO Box 1530 Hickory, NC 28603-1530 USA Phone 1.888.442.TAPE (8273) Fax 800.335.7651  
www.shurtape.com

**ISO 9000 CERTIFIED QUALITY SYSTEM**

release more than very small quantities, e.g., minute or trace amounts of a hazardous chemical, and does not pose a physical hazard or health risk to employees.”

This information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable for their circumstances.